

Pompen - Index - Technische gegevens

DOMPELPOMPEN FS-SERIE (A= vlotter, R=vlakzuigkraag)

TYPE		Vermogen P2, kW	I nom. A	Spanning V	Pers Inch	Debiet m3/u (max.)	Opv. Hoogte mwk (max.)	Doorkaat mm.	Gewicht kg	Kabel mtr.
FS 250		0,25 KW	1.8 A	230 V	1,5"	12 m3/u	8,5 m	6 mm	12 kg	10
FS 250A										A
FS 400		0,40 KW	3.6 A	230 V	2"	14,4 m3/u	11 m	6 mm	12 kg	10
FS 400A										A
FSR 400		0,40 KW	3.6 A	230 V	2"	14,4 m3/u	11 m	2 mm	15 kg	10
FS 750		0,75 KW	7.0 A	230 V	2"	19,2 m3/u	15 m	8 mm	15 kg	10
FS 750A										A
FS 1500		1,5 KW	10.0 A	230 V	2"	27 m3/u	22 m	9 mm	26 kg	10
FS 215		1,5 KW	3,2 A	400 V	2"	27 m ³ /u	22 m	9 mm	34 kg	20 m
FS 215 S	230 V	1,5 KW	10.0 A	230 V	2"	27 m ³ /u	22 m	9 mm	34 kg	20 m
FS 315		1,5 KW	3.2 A	400 V	3"	39 m ³ /u	16 m	9 mm	34kg	20 m
FS 315 S	230 V	1,5 KW	10.0 A	230 V	3"	39 m ³ /u	16 m	9 mm	34kg	20 m
FS 222		2,2 KW	4.8 A	400 V	2"	30 m ³ /u	27 m	9 mm	36 kg	20 m
FS 322		2,2 KW	4.8 A	400 V	3"	48 m ³ /u	20 m	9 mm	36 kg	20 m
FS 237		3,7 KW	8.0 A	400 V	2"	30 m ³ /u	36 m	11 mm	45 kg	20 m
FS 337		3,7 KW	8.0 A	400 V	3"	54 m ³ /u	30 m	11 mm	45 kg	20 m
FS 437		3,7 KW	8.0 A	400 V	4"	90 m ³ /u	18 m	11 mm	45 kg	20 m
FS 355		5,5 KW	12.0 A	400 V	3"	72 m ³ /u	32 m	11 mm	50 kg	20 m
FS 455		5,5 KW	12.0 A	400 V	4"	102 m ³ /u	22 m	11 mm	50 kg	20 m
FS 475		7,5 KW	16.0 A	400 V	4"	96 m ³ /u	42 m	15 mm	86 kg	20 m
FS 675		7,5 KW	16.0 A	400 V	6"	132 m3/u	31 m	15 mm	86 kg	20 m
FS 4110		11 KW	24.0 A	400 V	4"	102 m3/u	51 m	15 mm	86 kg	20 m
FS 6110		11 KW	24.0 A	400 V	6"	150 m3/u	32 m	15 mm	86 kg	20 m

LICHTGEWICHT DOMPELPOMPEN FLS-SERIE - Alu pompen (A= vlotter)

TYPE		Vermogen P2, kW	I nom. A	Spanning V	Pers Inch	Debiet m3/u (max.)	Opv. Hoogte mwk (max.)	Doorkaat mm.	Gewicht kg	Kabel mtr.
FLSR 400		0,40 KW	3.6 A	230 V	1"	8 m3/u	11 m	2 mm	12 kg	10 m
FLS 400		0,40 KW	3.6 A	230 V	2"	14 m3/u	11 m	6 mm	12 kg	10 m
FLS 400A										A
FSS 750		0,75 KW	7.0 A	230 V	2"	18 m3/u	15 m	8 mm	14 kg	10 m
FLS 750A										A

VUILWATERPOMPEN BV-SERIE (A= vlotter)

TYPE	Vermogen P2, kW	I nom. A	Spanning V	Pers Inch	Debiet m3/u (max.)	Opv. Hoogte mwk (max.)	Doorlaat mm.	Gewicht kg	Kabel mtr.
BV 204	0,4KW	3,6A	230 V	2"	14,4m3/u	11 m	45 mm	17 kg	10 m
BV 204 A									A
BV 208	0,75KW	7,0A	230 V	2"	20,4m3/u	13 m	45 mm	21 kg	10 m
BV 208A			230 V						A
BV 215	1,5KW	10,0 A	230 V	2"	27,6m3/u	17 m	45 mm	26 kg	10 m
BV 315	1,5KW	10,0A	230 V	3"	33m3/u	15 m	45 mm	26 kg	10 m
BV 215T	1,5KW	3,2A	400 V	2"	27,6m3/u	17 m	45 mm	26 kg	20 m
BV 315T	1,5KW	3,2A	400 V	3"	33m3/u	15 m	45 mm	26 kg	20 m
BV 322T	2,2KW	5,0A	400 V	3"	46m3/u	17 m	50 mm	38 kg	20 m
BV 337T	3,7KW	8,3A	400 V	3"	72m3/u	19 m	50 mm	47 kg	20 m
BV 455T	5,5KW	12,4A	400 V	4"	78m3/u	24 m	50 mm	66 kg	20 m

ROESTVRIJ STALEN POMPEN FSS-SERIE

TYPE	Vermogen P2, kW	I nom. A	Spanning V	Pers Inch	Debiet m3/u (max.)	Opv. Hoogte mwk (max.)	Doorlaat mm.	Gewicht kg	Kabel mtr.
FSS250	0,25KW	1,8A	230V	1,5"	12m3/u	8,5 m	6 mm	12 kg	10 mm
FSS400	0,40KW	3,6A	230V	2"	14,4m3/u	11 m	6 mm	12 kg	10 mm
FSS750	0,75KW	7,0A	230V	2"	19,2m3/u	15 m	8 mm	15 kg	10 mm

DWEILPOMP MET VLOTTE EN SENSOR

TYPE	Vermogen P2, kW	I nom. A	Spanning V	Pers Inch	Opv. Hoogte mwk (max.)	Gewicht kg
Sensoflat "C 240WF"	0,27KW	1,5 A	230V	BSP G 1"	8,0 m	5,4 kg
Snelheid : 28501/m						

**Uw verdeler "pompen" :
Werfix Bvba**

